

PRODUCT PROFILE

AC Input, Dual Outputs, Cable Comms PSU



- **Efficiency 80%.**
- **Input Protected.**
- **600W Output Power.**
- **Harsh Environment.**

Outstanding Quality, Value and Customer Service

GENERAL SPECIFICATION

- ◆ 192 V AC ~ 264 V AC @ 47 - 53 Hz Input.
- ◆ Output Voltages: +54.6 V DC @ 10A, 12V DC @ 3A.
- ◆ Operating Temperature Range -15°C to +45°C.
- ◆ Output Power: 600W.
- ◆ Power Factor 0.99 Active PFC.
- ◆ Weight 3Kg.
- ◆ Ripple <2mV RMS up to 800Hz.
- ◆ Line Regulation 0.1% & Load Regulation 0.5%.
- ◆ Through-hole Technology utilised.
- ◆ Designed to Harsh Environments, EN 55022 / EN 60555.
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements.

XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH
Tel +44 (0) 1233 623404 Fax +44 (0) 1233 641777
Email:sales@xcelpower.demon.co.uk
Visit our website: www.xcelpower.com

ISO 9001 Accredited

Other/ Comms