

PRODUCT PROFILE

HV & LV, Multiple Outputs, Civil Head-up Display PSU



- **Modular Solution.**
- **Complex Control Circuitry.**
- **Short Circuit Protection.**
- **Avionics / Civil Applications.**

Outstanding Quality, Value and Customer Service

Airborne

GENERAL SPECIFICATION

- ◆ 28 V DC Input.
- ◆ Multiple Outputs +5V @ 3.3A, +5V @ 0.7A, ±6.3V @ 1A, 1.25A, ±15V @ 1A, ±20V @ 2A (5.7A Pk), ±60V @ 1mA, 20mA, 890V @ 10µA, 3 ~ 5KV @ 400µA.
- ◆ Operating Temperature Range -40°C to +85°C.
- ◆ Weight <2.6Kg.
- ◆ Complex Control Circuitry.
- ◆ Combined SM and Through-hole Technology utilised..
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.
- ◆ Dimensions: 180 x 77 x 172 (mm).

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements.

XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH
Tel: +44 (0) 1233 623404 Fax: +44 (0) 1233 641777
Email: sales@xcelpower.demon.co.uk
Visit our website: www.xcelpower.com

ISO 9001 Accredited