

## PRODUCT PROFILE

### HV/LV Towed Decoy Power Supply



- **Lightweight.**
- **Efficiency >74%.**
- **Short Circuit Protection.**
- **Isolated HV Output.**

Outstanding Quality, Value and Customer Service

Airborne

### GENERAL SPECIFICATION

- ◆ 200 V DC ~ 310 V DC Input.
- ◆ Multiple Outputs +5V @ 0.3A, 6.3V @ 1.8A, +8V @ 0.25A, -8V @ 0.2A, +8V (Switched) @ 2.7A.
- ◆ Operating Temperature Range -40°C to +117°C.
- ◆ Short Circuit Protection.
- ◆ Efficiency >74%.
- ◆ Weight 220g.
- ◆ Isolated HV Output.
- ◆ Surface Mount Technology utilised.
- ◆ Designed to meet High Vibration Levels.
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements.

#### XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH  
Tel: +44 (0) 1233 623404 Fax: +44 (0) 1233 641777  
Email: sales@xcelpower.demon.co.uk  
Visit our website: www.xcelpower.com

ISO 9001 Accredited