

PRODUCT PROFILE

High Powered LITE PSU



- **Efficiency >65%.**
- **Noise & Ripple <50mV.**
- **Lightweight.**
- **High Power.**

Outstanding Quality, Value and Customer Service

GENERAL SPECIFICATION

- ◆ 28 V DC Battery Input (Nominal).
- ◆ Output Voltages ranging from +11V DC @ 5A to +!4V DC @ 5A.
- ◆ Operating Temperature Range -31°C to +55°C.
- ◆ Output Power 20W.
- ◆ Efficiency >65%.
- ◆ Weight <250g.
- ◆ Noise & Ripple <50mV.
- ◆ Through-Hole Technology utilised.
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.
- ◆ Dimensions: 91 x 41 x 75 (mm).

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements

XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH
Tel +44 (0) 1233 623404 Fax +44 (0) 1233 641777
Email:sales@xcelpower.demon.co.uk
Visit our website: www.xcelpower.com

ISO 9001 Accredited