

PRODUCT PROFILE

Helicopter Mounted Helmet Display Power Supply



- **Lightweight.**
- **Efficiency >50%.**
- **Low Profile.**
- **Isolated HV Output.**

Outstanding Quality, Value and Customer Service

Airborne

GENERAL SPECIFICATION

- ◆ 28 V DC Input (MIL-STD 704D compliant).
- ◆ Multiple Outputs $\pm 5V @ 1.7A$, $11V @ 200mA$, $\pm 15V @ 0.5A$, $1KV @ 20\mu A$, $2off 2.6KV @ 375\mu A$, $13KV @ 500\mu A$.
- ◆ Operating Temperature Range $-40^{\circ}C$ to $+70^{\circ}C$.
- ◆ Efficiency >50%.
- ◆ Weight 930g.
- ◆ Isolated HV Output.
- ◆ Surface Mount Technology utilised.
- ◆ Designed to meet High Vibration Levels.
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.
- ◆ Dimensions: 190 x 45 x 125 (mm).

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements.

XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH
Tel: +44 (0) 1233 623404 Fax: +44 (0) 1233 641777
Email: sales@xcelpower.demon.co.uk
Visit our website: www.xcelpower.com

ISO 9001 Accredited