

PRODUCT PROFILE

LV, Multi-Function Airborne Display Power Supply



- **High Reliability**
- **Over Voltage Protection.**
- **Over Temperature Sensor.**
- **BITE Capability.**

Outstanding Quality, Value and Customer Service

GENERAL SPECIFICATION

- ◆ 115 VAC 3 Phase - Aircraft Supply (MIL-STD-704A & BS.3G.100).
- ◆ Multiple Outputs: +3.3V DC @ 6A , +5V(L) DC @ 4A, ±5V(A) @ 0.5A, ±15V @1A, +42V DC @ 1.82A, +95/48V DC @ 0.81A
- ◆ Operating Temperature Range -40°C to +90°C.
- ◆ Over Voltage Protection.
- ◆ BITE Capability.
- ◆ Weight 0.75Kg.
- ◆ Over Temperature Sensor.
- ◆ Surface Mount Technology utilised.
- ◆ 50mS Hold Up.
- ◆ Custom In-house Design - Mechanical, PCB, Electrical & Electronic.

Note: All data is subject to change, and our Technical Sales Department should be consulted regarding any specific requirements.

XCEL Power Systems Ltd.

Brunswick Rd, Cobbs Wood, Ashford, Kent, UK. TN23 1EH
Tel: +44 (0) 1233 623404 Fax: +44 (0) 1233 641777
Email: sales@xcelpower.demon.co.uk
Visit our website: www.xcelpower.com

ISO 9001 Accredited

Airborne